

PRODUCT DATA

Product Description: Dakota Wrap

Dakota Wrap is a 100% pure bleached cellulose which has been specially designed for tube wrap applications.

Typical Values:

Property	Standard	+/-	Value
Substance gsm	ISO 536	5%	115
Caliper μm	ISO 534	5%	154
Bulk cm^2/g	ISO 534	-	1.34
CIE Whiteness %	ISO 11475	3%	86
Moisture %	ISO 287	1%	7.5
Roughness (Bendsten) both sides ml/min	ISO 8791-2	200ml/min	600
Cobb (60s) both sides gsm	ISO 535	5gsm	25

Printing and Finishing:

- Full colour litho
- Aqueous coating
- Foil Blocking
- Embossing
- Specially adapted to use on automated packaging lines with high productivity.

Storage:

- Store in a cool, dry environment out of direct sunlight @ 22°C (+/-2°C); relative humidity 50% (+/- 5%).
- Products should be stored in their original packaging until the time they are to be used.
- The paper should be allowed to acclimate to the environment of the workroom for 24 hours.

All statements, technical information and recommendations about Slater Harrison products are based on tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold on the basis that the purchaser shall make their own tests to determine the suitability of such products for their particular applications and uses, and that the purchaser assumes all risks and liabilities for the results of the use of the products, including use in accordance with the seller's recommendations. No salesman, representative or agent of Slater Harrison is authorised to give any guarantee, warranty or make any representation contrary to the above.